

## CLAIMS

What is claimed is:

Sub  
a1

1. A method for transmitting signals comprising:  
transmitting a data signal over a first wavelength on a single fiber strand;  
and  
transmitting a radio frequency signal over a second wavelength on the  
same single fiber strand.
2. The method of claim 1 further comprising:  
transmitting a plurality of other data signals over the first wavelength; and  
transmitting a plurality of other radio frequency signals over the second  
wavelength.
3. The method of claim 1 further comprising transmitting a plurality of  
other data signals and other radio frequency signals over other wavelengths on the single  
fiber strand.
4. The method of claim 1 further comprising transmitting another data  
signal over a third wavelength on the single fiber strand.
5. The method of claim 1 further comprising transmitting another radio  
frequency signal over a third wavelength on the single fiber strand.
6. The method of claim 1 wherein the data signal comprises an ethernet  
based signal.
7. The method of claim 1 wherein the data signal comprises an  
asynchronous signal.

8. The method of claim 1 wherein the data signal comprises a synchronous optical network based signal.

9. The method of claim 1 wherein the data signal comprises an optical carrier based signal.

10. The method of claim 1 wherein the radio frequency signal comprises a personal communication service signal

11. The method of claim 1 wherein the radio frequency signal comprises a local multipoint distribution system signal

12. The method of claim 1 wherein the radio frequency signal comprises a multipoint multichannel distribution service signal.

13. The method of claim 1 wherein the radio frequency signal comprises an unlicensed radio frequency spectrum signal.

14. The method of claim 1 further comprising connecting the data signal from the first wavelength to a third wavelength.

15. The method of claim 1 further comprising connecting the radio frequency signal from the second wavelength to a third wavelength.

16. The method of claim 1 further comprising connecting the data signal from a first path to a second path.

17. The method of claim 1 further comprising connecting the radio frequency signal from a first path to a second path.

sitting signals comprising  
 of data signals, e  
 ple fiber strand; and  
 of radio frequency  
 lengths on the same

transmitting a plurality of data signals, each over a corresponding

wavelength on a single fiber/strand; and

transmitting a plurality of radio frequency signals, each over other

corresponding wavelengths on the same single fiber strand.

1. The first of the four is the fact that the  
 2. second of the four is the fact that the  
 3. third of the four is the fact that the  
 4. fourth of the four is the fact that the

5

19. A system for transmitting signals comprising:  
a first node configured to transmit a data signal over a first wavelength on a single fiber strand and a radio frequency signal over a second wavelength on the same single fiber strand; and  
a second node configured to receive the data signal over the first wavelength and the radio frequency signal over the second wavelength.
20. The system of claim 19 wherein the first node comprises at least one member of a group comprising a switch, a cross connect, a fiber optic transmitter, and a fiber optic receiver.
21. The system of claim 20 wherein the cross connect comprises:  
a data matrix configured to connect the data signal over a path; and  
a radio frequency matrix configured to connect the radio frequency signal over another path.
22. The system of claim 19 wherein the first node comprises an optical device configured to transmit a mixed optical profile over the single fiber strand.
23. The system of claim 19 wherein the first node comprises at least one member of a group comprising a service node and a point of presence.
24. The system of claim 19 wherein the second node comprises at least one member of a group comprising a switch, a cross connect, a fiber optic transmitter, and a fiber optic receiver.

25. The system of claim 24 wherein the cross connect comprises:  
a data signal matrix configured to connect the data signal over a path; and  
a radio frequency matrix configured to connect the radio frequency signal  
over another path.
26. The system of claim 19 wherein the second node comprises an  
optical device configured to receive a mixed optical profile over the single fiber strand.
27. The system of claim 19 wherein the second node comprises at least  
one member of a group comprising a service node and a point of presence.
28. The system of claim 19 wherein the second node further is adapted  
to transmit the data signal on a third wavelength and to transmit the radio frequency  
signal on a fourth wavelength.
29. The system of claim 28 wherein the third wavelength and the fourth  
wavelength are on another single fiber strand.
30. The system of claim 19 wherein the first node further is adapted to  
receive the data signal on a third wavelength and to receive the radio frequency signal on  
a fourth wavelength.
31. The system of claim 30 wherein the third wavelength and the fourth  
wavelength are on another single fiber strand.

32. A system for transmitting signals comprising:  
a device configured to transmit a data signal over a first wavelength on a  
single fiber strand and to transmit a radio frequency signal over a  
second wavelength on the same single fiber strand.

15

33. A system for transmitting signals comprising:

a data matrix configured to transmit a data signal over a first wavelength

on a single fiber strand; and

a radio frequency matrix configured to transmit a radio frequency signal

over a second wavelength on the same single fiber strand.

34. The system of claim 33 wherein the data matrix comprises:

a transmitter configured to transmit the data signal over the first

wavelength; and

a receiver configured to receive the data signal over a third wavelength

and to connect the data signal to the transmitter.

35. The system of claim 34 wherein the first wavelength and the third

wavelength are the same.

36. The system of claim 33 wherein the radio frequency matrix

comprises:

a transmitter configured to transmit the radio frequency signal over the

second wavelength; and

a receiver configured to receive the radio frequency signal over a third

wavelength and to connect the data signal to the transmitter.

37. The system of claim 36 wherein the second wavelength and the third wavelength are the same.

38. The system of claim 35 wherein the radio frequency matrix comprises a jumper connecting the receiver to the transmitter.

39. The system of claim 33 wherein the data matrix further is configured to transmit a plurality of other data signals, each over another corresponding wavelength on the single fiber strand.

40. The system of claim 36 wherein the data matrix comprises:

a plurality of transmitters each configured to transmit one of the other data signals over the other corresponding wavelength; and

a plurality of receivers each configured to receive one of the other data signals over a different corresponding wavelength and to connect the data signals to one of the transmitters.

41. The system of claim 33 wherein the radio frequency matrix further is configured to transmit a plurality of other radio frequency signals, each over other corresponding wavelengths on the same single fiber strand.



5

a plurality of receivers each configured to receive one of the other radio frequency signals over a different corresponding wavelength and to connect the radio frequency signals to one of the transmitters.